# P8 Printer

faster, smaller, quieter printing from Hypercom

Hypercom® P8 family printers offer higher performance, greater reliability and lower operating costs, making them superior to any other printer on the market.

### P8 Features:

- ☐ Bi-directional printing improves print speeds
- Quiet operation
- Easy-to-load pre-printed or plain roll paper
- Paper Out and Power indicator lights
- Extra wide 3-inch roll
- Small footprint
- Compatible with all Hypercom T7 terminals


**P8** printers are available in either 40-column friction feed (P8F) or 23-column sprocket feed (P8S) models, making them a sensible choice for printing credit card vouchers.

The P8F roll printer helps speed transaction times with rapid paper advance at the rate of 13 lines per second.

The P8S sprocket feed printer provides printing on pre-printed forms. These are particularly suitable for custom applications that require printing of large amounts of standard text or complex International character sets. With paper advanced at a rapid 16 lines per second, customers are not kept waiting. Paper loading is simple and easy with both Hypercom printers.

In addition, both P8 printers provide quality receipts in a new, compact, quiet design. P8 printers are powered by the terminal,

eliminating the need for separate power supplys and outlets.









# P8 Specifications

<u>P8F</u> <u>P8</u>

Printer Type Friction feed with 40 columns Sprocket feed with 23 columns

**Paper** 3.0 in - 3.35 in/76 mm - 85 mm 3.0 in/76 mm

1, 2 or 3-ply carbonless 1, 2 or 3-ply carbonless

Font 7x7 impact dot matrix 5x7 impact dot matrix

Print direction Bi-directional Bi-directional

**Print speed** 4 lines per second 4 lines per second

Feed speed 13 lines per second 16 lines per second

Character size (w/h)  $1.59 \times 2.87 \text{ mm}$   $1.97 \times 2.87 \text{ mm}$ 

Line spacing 1/6 in 1/6 in

Ribbon life (black) 1,200,000 characters 1,200,000 characters

Ribbon size 13 mm 13 mm

**Operating temperature** 0-45 C/32-113 F 0-45 C/32-113 F

**Printer reliability** 2,000,000 lines MTBF 2,000,000 MTBF

**Head life** 50,000,000 characters 50,000,000 characters

ESD resistance 12,000 volts 12,000 volts

Ribbon RC2001B RC2001B

**Star number** 30980120 30980120

**Dimensions** 5.5 in x 9.0 in x 4.25 in/ 5.5 in x 8.0 in x 5.0 in/

 $13.97 \text{ cm} \times 22.86 \text{ cm} \times 10.79 \text{ cm}$   $13.97 \text{ cm} \times 20.32 \text{ cm} \times 12.7 \text{ cm}$ 

**Weight** 2.25 lbs/0.84 kg 2.25 lbs/0.84 kg

**Power** 24 Vdc, IA supplied by terminal 24 Vdc, IA supplied by terminal

#### WORLD HEADQUARTERS/ NORTH AMERICA

Hypercom Corporation 2851 W. Kathleen Road Phoenix, Arizona 85053 USA

TEL: +1.602.504.5000 FAX: +1.602.504.4578

# LATIN AMERICA

Hypercom Latin America Rua Joaquim Floriano 72 16° andar Cj161 04534-000 ItaimBibi São Paulo, Brazil TEL: +55.11.3365.2600 FAX: +55.11.3365.2610

# ASIA/PACIFIC RIM

Hypercom Asia Ltd. 21/F Metro Centre II 21 Lam Hing Street Kowloon Bay Hong Kong TEL: +852.2561.6800 FAX: +852.2561.5890

#### EUROPE, MIDDLE EAST, AFRICA

Hypercom Europe Ltd. Unit 2, Woking Eight Forsyth Road Woking, GU21 5SB United Kingdom TEL: +44.1.483.718600 FAX: +44.1.483.718601



www.hypercom.com 1.877.840.9820

©2001 Hypercom Corporation, all rights reserved. Hypercom, the Hypercom logo and ICE-PAC are registered trademarks of Hypercom Corporation. The Global Leader in Electronic Transaction Solutions is a trademark of Hypercom Corporation. All other products or services mentioned in this document are trademarks, service marks, registered trademarks or registered service marks of their respective owners.

Hypercom Corporation (NYSE: HYC) is a leading global provider of electronic payment solutions that add value at the point-of-sale for consumers, merchants and acquirers. Hypercom products include secure card payment terminals and web applications, networking equipment and software applications for e-commerce, m-commerce, smart cards and traditional payment applications.