



The LinkPoint® AIO terminal supports the complex processing demands of today's merchants with a sophisticated all-in-one solution. Its state-of-the-art technology addresses the full range of payment capabilities, including multiple merchant applications and identifications. The high-performance LinkPoint AIO terminal delivers quick transaction times and superior reliability to merchants' customers — all at an affordable price. An intuitive ATM-style interface makes the LinkPoint AIO terminal easy to learn and easy to use. Its screen-addressable keys and dedicated function keys offer more selections with fewer steps. Its high-speed, integrated thermal printer streamlines sales, installation and everyday merchant operation. Compatible with many industry-standard peripherals, the LinkPoint AIO terminal provides maximum versatility at the merchant site.

Superior Reliability

- Reduces long-term merchant support expenses
- 12-month warranty provides peace of mind

Unbeatable Performance

- Fast, secure processing keeps pace with merchants' transaction needs
- Supports all payment processing methods, including credit, debit, EBT, checks, gift card, stored value and loyalty
- Thermal printer provides quick, legible receipts at over 15 lines per second

Maximum Merchant Efficiency

- Intuitive ATM-style interface makes learning a snap
- Clearly labeled, dedicated function keys simplify everyday operations
- Screen-addressable keys provide more selections with fewer steps
- Two-line display is easy to read in all lighting conditions
- Reliable thermal printer with drop-in paper-loading system is quick and hassle free

Versatility at the Merchant Site

- Supports multiple applications, languages and multiple merchant identifications
- Calculator function provides added value
- Compatible with many industry-standard peripherals, including PIN pads and check readers



Compact Design

- Small footprint with base or wall mounting saves valuable counter space
- A single power supply reduces cable clutter

Advanced Fraud Prevention

- Password protection prevents unauthorized downloads
- Manager password controls ensure transaction security

Specifications

- **Terminal:** Memory: 1 MB total; 512K battery-backed RAM; 512K flash. Operating system embedded in flash sector. Microprocessor: Z180 CPU.
- **Screen:** Two-line, 20-character backlit LCD.
- **Card reader:** Track 1 and track 2, bidirectional; track 1, 2 and 3 reader available upon special order.
- **Peripheral ports:** 6-pin DIN port for PIN pads, smart-card readers or bar-code wands, 8-pin DIN RS-232 general-purpose port for check readers, etc.
- **Printer:** Easy drop-in paper loading system with a fixed thermal print head. Speed: 15+ lines per second. Paper: Standard 2 1/4" (58mm) thermal roll (Appleton 1012 sheet is

recommended). Paper Roll Diameter: 1.9 in (48mm) maximum. Open-cover/paper-out sensor. Supports graphic printing capability and 13 international character sets. Mechanical Life: 15 million lines.

- **Communications:** Modem: Standard asynchronous/synchronous; 300/1,200/2,400 bps standard Bell 103/212A, V.22 BIS. Telco: Standard RJ-11 modular jacks (2) located on base of unit.
- **Physical:** 3.16 in. (80.32 mm) H x 5.86 in. (149 mm) W x 9.66 in. (244 mm) L, 1.25 lb. (0.54 kg). Net weight (terminal only): 1.51 lb. (0.68 kg). Net shipping weight (including power adapter): 3.4 lb. (1.54 kg).
- **Power:** 100-240 VAC, 50/60 Hz, .8A (switching power supply). Power consumption: 350 mA, off hook, 2 A during printing. Power adapter output: 7.5 VDC, 3 A (22.5W).
- **Environmental:** Storage temperature: 32° to 104°F (0° to 40°C). Operating humidity: 10% to 90%, noncondensing.

For more information, please contact us at 1-800-634-7221.